



EQ6000 Plus

HIGH VOLTAGE STORAGE BATTERY



- 5.99kWh capacity
- Scalable to 41.93kWh
- 90% Depth of Discharge
- Large temperature tolerance
- CAN communication



HIGH
VOLTAGE



EASY
INSTALLATION



HIGH
EFFICIENCY



EXPANDABLE
SYSTEM



90%
DOD

The EQ is a high-performance, scalable battery storage system. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 41.93kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.



For more information about the Fox ESS range, visit:
www.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	EQ6000 Plus -L2	EQ6000 Plus -L3	EQ6000 Plus -L4	EQ6000 Plus -L5	EQ6000 Plus -L6	EQ6000 Plus -L7
ELECTRICAL CHARACTERISTICS						
Battery Type	LFP (LiFePO ₄)					
Battery Module	1*EQ6000 Plus-M 1*EQ6000 Plus-S	1*EQ6000 Plus-M 2*EQ6000 Plus-S	1*EQ6000 Plus-M 3*EQ6000 Plus-S	1*EQ6000 Plus-M 4*EQ6000 Plus-S	1*EQ6000 Plus-M 5*EQ6000 Plus-S	1*EQ6000 Plus-M 6*EQ6000 Plus-S
Nominal Capacity [kWh]	11.98	17.97	23.96	29.95	35.94	41.93
Nominal Voltage [V]	115.2	172.8	230.4	288.0	345.6	403.2
Operating Voltage [V]	104.4 ~ 131.4	156.6 ~ 197.1	208.8 ~ 262.8	261.0 ~ 328.5	313.2 ~ 394.2	365.4 ~ 459.9
Max. Charge/Discharge Current [A] ¹	50					
Peak Discharge Current [A]	65 @60sec					
Battery Pack Round-Trip Efficiency [%]	>95					
Depth of Discharge [%]	90					
Communication	CAN					
Display	EQ6000 Plus-S: LED*1, EQ6000 Plus-M: LED*6					
Scalability	Max. 7 Modules in Series					
OPERATING CONDITIONS						
Installation Location	Outdoor/ Indoor (Stand)					
Operating Temperature [°C]	Charge: 0 ~ 55, Discharge: -10 ~ 55					
Operating Temperature [°C] (warm up function on, optional)	Charge: -25 ~ 55, Discharge: -25 ~ 55					
Storage Temperature [°C]	-10 ~ 40					
Cooling Method	Natural Convection					
Humidity [%]	5 ~ 95 (No Condensation)					
Altitude [m]	Max. 3,000					
PROTECTION						
Fire Protection Function	YES					
MECHANICAL CHARACTERISTICS						
Dimensions (W*H*D) [mm]	660*420*360	660*575*360	660*730*360	660*885*360	660*1040*360	660*1195*360
Weight [kg]	111.2	161.2	211.2	261.2	311.2	361.2
CERTIFICATES						
Safety	IEC 62619					
EMC	IEC 61000-6-1/2/3/4					
Transportation	UN38.3					
Ingress Protection	IP65					

*1, The current is affected by temperature ,cell voltage and SOC.