

# EQ5500

## HIGH VOLTAGE STORAGE BATTERY

The EQ is a high-performance, scalable battery storage system. Its modular design enables maximum flexibility, making it suitable for a wide range of storage applications. Additional batteries can be installed in series, allowing for a maximum storage capacity of 49.14kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.



- 5.46kWh capacity
- Scalable to 49.14kWh
- 90% Depth of Discharge
- Large temperature tolerance
- CAN communication



**HIGH  
VOLTAGE**



**EASY  
INSTALLATION**



**HIGH  
EFFICIENCY**



**EXPANDABLE  
SYSTEM**



**90%  
DOD**



# TECHNICAL SPECIFICATIONS

MODEL	EQ5500 -L2	EQ5500 -L3	EQ5500 -L4	EQ5500 -L5	EQ5500 -L6	EQ5500 -L7	EQ5500 -L8	EQ5500 -L9
<b>ELECTRICAL CHARACTERISTICS</b>								
Battery Type	LFP (LiFePO <sub>4</sub> )							
Battery Module (EQ5500-M)	1							
Battery Module (EQ5500-S)	1	2	3	4	5	6	7	8
Nominal Energy [kWh]	10.92	16.38	21.84	27.30	32.76	38.22	43.68	49.14
Nominal Voltage [V]	89.6	134.4	179.2	224.0	268.8	313.6	358.4	403.2
Operating Voltage [V]	81.2 ~ 102.2	121.8 ~ 153.3	162.4 ~ 204.4	203.0 ~ 255.5	243.6 ~ 306.6	284.2 ~ 357.7	324.8 ~ 408.8	365.4 ~ 459.9
Recommend Charge/Discharge Current [A]	50							
Max. Charge/Discharge Current [A] <sup>*1</sup>	50							
Peak Discharge Current (60S) [A]	65							
Battery Pack Round-Trip Efficiency [%]	>95							
Depth Of Discharge [%]	90							
Communication	CAN							
Display	EQ5500-S: LED*1, EQ5500-M: LED*6							
Scalability	Max. 9 Modules in Series							
<b>OPERATING CONDITIONS</b>								
Installation Location	Outdoor/ Indoor (Stand)							
Operating Temperature [°C]	Charge: 0 ~ 55, Discharge: -10 ~ 55							
Operating Temperature [°C] (warm up function on, optional)	Charge: -25 ~ 55, Discharge: -25 ~ 55							
Storage Temperature [°C]	-10 ~ 35							
Cooling Method	Natural Convection							
Humidity [%]	5 ~ 95 (No Condensation)							
Altitude [m]	Max. 3,000							
<b>PROTECTION</b>								
Fire Protection Function	YES							
<b>MECHANICAL CHARACTERISTICS</b>								
Dimensions (W*D*H) [mm]	570*380							
	*386	*524	*662	*800	*938	*1076	*1214	*1352
Weight [kg] (±5%)	85	126	167	208	249	290	331	372
Cell Net Weight [kg] (±5%)	56.6	84.8	113.1	141.4	169.7	198.0	226.2	254.5
<b>CERTIFICATES</b>								
Safety	IEC 62619							
EMC	EN IEC 61000-6-1/2/3/4							
Transportation	UN38.3							
Ingress Protection	IP65							

\*1 The current is affected by temperature, cell voltage and SOC.