

T-MAX PLUS

COMMERCIAL AND INDUSTRIAL ENERGY STORAGE SYSTEM

The T-MAX Plus Series accommodates "All-in-one" design philosophy, integrating battery with longevity, intelligent BMS, high performance PCS, preventive safety system, smart distribution system and heat dissipation management system into one standard container for standardized manufacturing (for outdoor application) and simpler installation.



50kW ...➡➡➡ 125kW



APPLICATION

Supports direct connection to grid, supplying stable power in on-grid mode.



SAFETY

Compartmentalized design with a preventive alarm system.



ECONOMIC

Zero power loss through efficient temperature control and frequency variation.



INTELLIGENT

Offers multiple operation modes, including Peak Shaving, Load Shedding, and Frequency Regulation. Operating data can be transmitted to Fox ESS Cloud via Ethernet or 4G.



AUGMENTABLE

Preconfigured during manufacturing, plug and play onsite. Capable of parallel connection upgrades for flexible system size application.

TECHNICAL SPECIFICATIONS

MODEL			TM241kWh- 50kW-AC	TM241kWh- 60kW-AC	TM241kWh- 80kW-AC	TM241kWh- 100kW-AC	TM241kWh- 125kW-AC
BATTERY SPECIFICATION							
Battery Type [V / Ah]					LFP 3.2 / 314		
Battery Pack Energy [kWh]					60.29		
Battery System Energy [kWh]					241		
Operating Voltage Range [V]					672 ~ 876		
Number of Temperature Sensors					128		
Max. Charging / Discharging Current [A]					190 / 190		
Battery Pack Protection Level					IP67		
AC OUTPUT (GRID)							
Nominal AC Output Power [kW]			50	60	80	100	125
Max. AC Output Power [kVA]			55	66	88	110	137.5
Nominal AC Output Current [A]	380V		76.0	91.2	121.6	152.0	190.0
	400V		72.2	86.6	115.5	144.4	180.4
Max. AC Output Current [A]	380V		83.6	100.3	133.7	167.2	198.5
	400V		79.4	95.3	127.0	158.8	198.5
Nominal AC Voltage [V]					220 / 380, 230 / 400, 3P4W		
AC Voltage Range					0.8*Un ~ 1.2*Un		
Nominal AC Frequency [Hz]					50 / 60		
Frequency Range [Hz]					50 / 60, ±5		
Power Factor					0.8 Leading ~ 0.8 Lagging		
Max. THDi [%]					< 3		
EFFICIENCY							
Max. Round Trip Efficiency [%]					91.5		
Max. Efficiency [%]					98.5		
PROTECTION							
DC Input Switch					YES		
AC Overcurrent Protection					YES		
AC Output Short Circuit Protection					YES		
AC / DC Surge Protection					Class II		
ISO Detection					YES		
Residual Current Detection					YES		
Ground Fault Detection					YES		
GENERAL SEPECIFICATION							
Dimensions (W * H * D) [mm]					1040 * 2230 * 1500		
Weight [kg]					< 2400		
Operating Temperature [°C]					-25 ~ 55		
Type of Cooling					Liquid Cooling		
Operating Altitude [m]					≤ 3000		
Humidity [%]					0 ~ 100		
Noise [dB]					<75 @ 1 m		
DOD [%]					0 ~ 100		
Cycle Life					≥ 8000 @ 70% EOL		
Communication Interfaces					Ethernet / 4G		
Ingress Protection					IP55		
Corrosion Protection					C5		
Fire Protection					Smoke Detector, Heat Detector, Alarm Sounder, Cabinet-Level / PACK-Level Aerosol, Explosion Vent		
PARALLEL UNITS							
Max. number of parallel units (On-grid) [pcs]					25		

* Only for on-grid mode. Off-grid mode and genset switching are not supported.