

EQ5000-P

HIGH VOLTAGE STORAGE BATTERY

The EQ is a high-performance, scalable battery storage system. Its modular design enables maximum flexibility, making it suitable for a wide range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 44.73kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.



- 4.97kWh capacity
- Scalable to 44.73kWh
- 100% Depth of Discharge
- Wide operating temperature range
- CAN communication



**HIGH
VOLTAGE**



**EASY
INSTALLATION**



**HIGH
EFFICIENCY**



**EXPANDABLE
SYSTEM**



**100%
DOD**



www.fox-ess.com

TECHNICAL SPECIFICATIONS

MODEL	EQ5000 -P-L2	EQ5000 -P-L3	EQ5000 -P-L4	EQ5000 -P-L5	EQ5000 -P-L6	EQ5000 -P-L7	EQ5000 -P-L8	EQ5000 -P-L9
ELECTRICAL CHARACTERISTICS								
Battery Type	LFP (LiFePO ₄)							
Battery Module (EQ5000-M-P)	1							
Battery Module (EQ5000-S-P)	1	2	3	4	5	6	7	8
Nominal Energy [kWh]	9.94	14.91	19.88	24.85	29.82	34.79	39.76	44.73
Nominal Voltage [V]	89.6	134.4	179.2	224.0	268.8	313.6	358.4	403.2
Operating Voltage[V]	81.2 ~ 102.2	121.8 ~ 153.3	162.4 ~ 204.4	203.0 ~ 255.5	243.6 ~ 306.6	284.2 ~ 357.7	324.8 ~ 408.8	365.4 ~ 459.9
Recommend Charge/Discharge Current [A]	50							
Max. Charge/Discharge Current [A] ^{*1}	50							
Peak Discharge Current (60S) [A]	65							
Battery Pack Round-Trip Efficiency [%] ^{*2}	>95							
Depth Of Discharge [%]	100							
Communication	CAN							
Display	EQ5000-S-P: LED*1, EQ5000-M-P: LED*6							
Scalability	Max. 9 Modules in Series							
OPERATING CONDITIONS								
Installation Location	Outdoor/ Indoor (Stand)							
Operating Temperature [°C] ^{*3}	Charge: 0 ~ 55, Discharge: -10 ~ 55							
Operating Temperature [°C] (warm up function on, optional)	Charge: -25 ~ 55, Discharge: -25 ~ 55							
Storage Temperature [°C]	-10 ~ 35							
Cooling Method	Natural Convection							
Humidity [%]	5 ~ 95 (No Condensation)							
Altitude [m]	Max. 3,000							
PROTECTION								
Fire Protection Function	YES							
MECHANICAL CHARACTERISTICS								
Dimensions (W*D*H) [mm]	570*380							
	*386	*524	*662	*800	*938	*1076	*1214	*1352
Weight [kg] (±5%)	85	126	167	208	249	290	331	372
Cell Net Weight [kg] (±5%)	56.6	84.8	113.1	141.4	169.7	198.0	226.2	254.5
CERTIFICATES								
Safety	IEC 62619							
EMC	EN IEC 61000-6-1/2/3/4							
Transportation	UN38.3							
Ingress Protection	IP65							

*1 The current is affected by temperature, cell voltage and SOC.

*2 @25°C, 0.3C charging/discharging.

*3 Charge and discharge power reduction applies at low temperatures.