

A SERIES

EV CHARGER



SOCKET VERSION



PLUG VERSION

- | | | |
|---------|-------|--------------|
| • A7300 | 7.3kW | SINGLE-PHASE |
| • A011K | 11kW | THREE-PHASE |
| • A022K | 22kW | THREE-PHASE |



ROBUST DURABILITY

IP55 and IK08 protection for reliable performance.



SMART CONNECTIVITY

Connect via Bluetooth, Wi-Fi, 4G, or Ethernet.



FLEXIBLE INTEGRATION

OCPP 1.6JSON or 2.0.1 compliant with an open MODBUS interface.



ADVANCED TECHNOLOGY

ISO15118(-2/-20) ready with dynamic load balancing.



SCHEDULED TIME CHARGING

Set the charging time as you wish.



RENEWABLE ENERGY COMPATIBILITY

Direct surplus solar power for EV charging.

TECHNICAL SPECIFICATIONS

MODEL	A7300P1-E-B	A011KP1-E-B	A022KP1-E-B	A7300S1-E-B	A011KS1-E-B	A022KS1-E-B
				A7300S-T2S-B	A011KS-T2S-B	A022KS-T2S-B
AC INPUT						
Wiring Scheme	L/N/PE	3L/N/PE	3L/N/PE	L/N/PE	3L/N/PE	3L/N/PE
Rated Input Voltage [Vac]	230±20%	400±20%	400±20%	230±20%	400±20%	400±20%
Rated Input AC Current [A]	32	16	32	32	16	32
Rated Input Frequency [Hz]	50/60					
Standby Power Consumption [W]	≤10					
AC OUTPUT						
Max. AC Power [kW]	7.3	11	22	7.3	11	22
Rated Output AC Current [A]	32	16	32	32	16	32
Power Accuracy [%]	≤2					
PROTECTION						
Electrical Protection	Over/Under Voltage Protection, Overcurrent Protection, Leakage Current, Ground Protection, Surge Protection, Overtemperature Protection, Tamper Protection, PEN					
Environmental Protection	Salt-mist-resistant, UV-resistant Treatment					
GENERAL DATA						
Connector Type	IEC 62196 Type 2 Cable, Type 2 Socket, Type 2 Socket With Shutter					
Bluetooth	Yes					
Wifi (2.4GHz)	Yes					
Ethernet (RJ45)	Yes					
OCPP 1.6 JSON or OCPP 2.0.1	Yes					
4G LTE ^[i]	Optional, SIM Card Size: Micro-SIM (3FF)					
ISO 15118	ISO15118-2 (AC) / ISO 15118-20 (AC & AC_BPT)					
RFID Reader	Mifare ISO/IEC 14443 A					
Start Mode	Plug&Charge/RFID Card/App					
Installation	Wall-mount / Post-mount					
Operating Temperature Range [°C]	-30 ~ +50					
Storage Temperature [°C]	-40 ~ +70					
Operating Humidity [%]	5 ~ 95 (No condensation)					
Operating Altitude [m]	<2000					
Dimensions (W*H*D) [mm]	190*320*130			190*320*144		
Net Weight [kg]	≤6.3			≤3.2		
Charging Cable Length [m]	6			/		
IP Protection Rating	Body-IP65, Socket-IP55					
IK Protection Rating	IK08					
Residual Current Detection*	AC 30mA+ DC 6 mA					
Cooling	Self Cooling					
EMC	Class B					
Certification	CE/CB/UKCA/RCM					
Certification Standard	EN/IEC 61851-1: 2019, EN/IEC 61851-21-2: 2021					

[1] Requires external SIM card (not included)
*Internal RCD-DD meets the trip time characteristics specified in IEC 62955
*External RCCB is required
*Select Type A or Type B according to local regulations