The Champion's Choice

Higher · Faster · Smarter

FOX ESS

EPS BOX PRO-G

THREE-PHASE



- Robust metal enclosure IP65
- Applied to residential solar installations
- Compatible with H3/ H3 Smart/PQ3 Plus inverter
- Automatically switch to On-Grid/ Off-Grid state

MAX. INPUT CURRENT 63A

EASY INSTALLATION

IP65 RATED

SAFETY

www.fox-ess.com

DATASHEET

TECHNICAL SPECIFICATIONS

MODEL	EPS BOX PRO-G
UTILITY SUPPLY	
Rated Voltage [VAC]	220/380, 230/400, 3L/N/PE
Rated Frequency [Hz]	50/60
Max. Input Current (Per Phase) [A]	63
INVERTER GRID	
Rated Voltage [VAC]	220/380, 230/400, 3L/N/PE
Rated Frequency [Hz]	50/60
Max. Input Current (Per Phase) [A]	25
INVERTER EPS	
Rated Voltage [VAC]	220/380, 230/400, 3L/N/PE
Rated Frequency [Hz]	50/60
Max. Input Current (Per Phase) [A]	25
LOAD	
Rated Voltage [VAC]	220/380, 230/400, 3L/N/PE
Rated Frequency [Hz]	50/60
Max. Output Current (Per Phase) [A]	63
GENERAL DATA	
Cooling Concept	Natural
Installation	Wall-mounted
Operating Temperature Range [°C]	-25 ~ +60 (derating at 45)
Dimensions (W*H*D) [mm]	550*420*138.5
Dimensions of packing (W*H*D) [mm]	665*515*235
Net Weight [kg]	9.3
Gross Weight [kg]	11
Ingress Protection	IP65