

ATTESTATION OF CONFORMITY

Issued to: FOXESS CO., LTD.
No.939, Jinhai Third Road, New Airport Industry Area, Longwan District, Wenzhou,
Zhejiang, China

For the product: Storage inverter

Trade name:



Type/Model: H3-5.0-E, H3-6.0-E, H3-8.0-E, H3-10.0-E, H3-10.0-E1, H3-12.0-E
AC3-5.0-E, AC3-6.0-E, AC3-8.0-E, AC3-10.0-E, AC3-10.0-E1, AC3-12.0-E

Ratings: See Annex

Manufactured by: FOXESS CO., LTD.
No.939, Jinhai Third Road, New Airport Industry Area, Longwan District, Wenzhou,
Zhejiang, China

Requirements: C10/11:2021 (Edition 2.2)

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6160265.50.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

Arnhem, 7 June 2023

Number: 6160265.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.

Kreny Lin
Certification Manager

A handwritten signature in black ink, appearing to read "Kreny Lin".

Page 1 of 3

© Integral publication of this attestation and adjoining reports is allowed

Document no. : 6160265.01AOC

Ratings of the test product:

Operating temperature range: - 25°C to + 60°C

Protective class: I

Ingress protection rating: IP65

Power factor range (adjustable): 0.8 leading...0.8 lagging

Over voltage category: III(AC), II(DC)

H3-5.0-E:

PV input: max 1000 Vdc, MPPT voltage range: 160-950 Vdc, max 14 A / 14 A, Isc PV: 16 A / 16 A

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 15.2 A, max apparent power 10000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 8.0 A, max active power 5000 W, max apparent power 5500 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 15.2 A, max apparent power 10000 VA

H3-6.0-E:

PV input: max 1000 Vdc, MPPT voltage range: 160-950 Vdc, max 14 A / 14 A, Isc PV: 16 A / 16 A

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 18.2 A, max apparent power 12000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 9.6 A, max active power 6000 W, max apparent power 6600 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 18.2 A, max apparent power 12000 VA

H3-8.0-E:

PV input: max 1000 Vdc, MPPT voltage range: 160-950 Vdc, max 26 A / 14 A, Isc PV: 32 A / 16 A

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 24.2 A, max apparent power 16000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 12.8 A, max active power 8000 W, max apparent power 8800 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 21.2 A, max apparent power 14000 VA

H3-10.0-E:

PV input: max 1000 Vdc, MPPT voltage range: 160-950 Vdc, max 26 A / 14 A, Isc PV: 32 A / 16 A

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 24.2 A, max apparent power 16000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 16.0 A, max active power 10000 W, max apparent power 11000 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 22.7 A, max apparent power 15000 VA

H3-10.0-E1:

PV input: max 1000 Vdc, MPPT voltage range: 160-950 Vdc, max 26 A / 14 A, Isc PV: 32 A / 16 A

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 24.2 A, max apparent power 16000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 16.0 A, max active power 10000 W, max apparent power 10000 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 22.7 A, max apparent power 15000 VA

H3-12.0-E:

PV input: max 1000 Vdc, MPPT voltage range: 160-950 Vdc, max 26 A / 14 A, Isc PV: 32 A / 16 A

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 24.2 A, max apparent power 16000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 19.2 A, max active power 12000 W, max apparent power 13200 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 22.7 A, max apparent power 15000 VA

AC3-5.0-E:

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 15.2A, max apparent power 10000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 8.0 A, max active power 5000 W, max apparent power 5500 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 15.2 A, max apparent power 10000 VA

AC3-6.0-E:

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

Document no. : 6160265.01AOC

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 18.2A, max apparent power 12000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 9.6 A, max active power 6000 W,
max apparent power 6600 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 18.2 A, max apparent power 12000 VA

AC3-8.0-E:

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 24.2A, max apparent power 16000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 12.8 A, max active power 8000 W,
max apparent power 8800 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 21.2 A, max apparent power 14000 VA

AC3-10.0-E:

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 24.2A, max apparent power 16000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 16.0 A, max active power 10000 W,
max apparent power 11000 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 22.7 A, max apparent power 15000 VA

AC3-10.0-E1:

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 24.2A, max apparent power 16000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 16.0 A, max active power 10000 W,
max apparent power 10000 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 22.7 A, max apparent power 15000 VA

AC3-12.0-E:

Battery: voltage range: 180-600 Vdc, type: Lithium battery, max charge/discharge current: 26 A / 26 A

AC input: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 24.2A, max apparent power 16000 VA

AC output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 19.2 A, max active power 12000 W,
max apparent power 13200 VA

EPS output: 220 / 380, 230 / 400 Vac, 3L / N / PE, 50 / 60 Hz, max 22.7 A, max apparent power 15000 VA

--- End ---