

ATTESTATION

of conformity with European Directives

BV LCIE CHINA Number 2166AS11AVSV43256

Product PV inverter (Grid-tied photovoltaic inverter)

Reference S700-G2, S1000-G2, S1500-G2, S2000-G2, S2500-G2, S3000-G2, S3300-G2

Issued to FOXESS CO.,LTD

Address

Room A203, Building C, No 205, Binhai Six Road, New Airport Industry Area, Longwan

District, Wenzhou, Zhejiang Province

Manufacturer FOXESS CO.,LTD

Technical characteristics See below table

The submitted sample of the above equipment has been tested for C marking according to following European Directive and following standards:

LVD Directive 2014/35/EU *

* Thanks to note that from April 20th 2016; this directive will be replaced by the new LVD directive, 2014/35/EU.

Standards	Report number	Report date
EN 62109-1:2010 EN 62109-2:2011	AVSV-ESH-P21091028-1 AVSV-ESH-P21091028-2	2021-11-05

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product

The CE marking may be affixed if all relevant and effective European Directives with CE are applicable

Shanghai (P.R. China), Nov 5th, 2021



Robin Wu

Project Manager

This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.

Version: 3.0 / Feb.10, 2021



Model / Type:	S700-G2	S1000-G2	S1500-G2		
MPP DC voltage range [V]:	50-480				
Max. Input DC voltage [V]:	500				
Max. Input DC current [A]:	14A				
Output AC voltage [V]::	220/230/240V, 50/60Hz				
Max. Output AC current [A]:	3,5	4,8	7,2		
Rated output power [W]:	700	1000	1500		

Model / Type:	S2000-G2	S2500-G2	S3000-G2	S3300-G2	
MPP DC voltage range [V]	50-480				
Max. Input DC voltage [V]	500				
Max. Input DC current [A]:	14A				
Output AC voltage [V]	. 220/230/240V, 50/60Hz				
Max. output AC current [A]	9,6	12,0	14,3	14,3	
Rated output power [VA]:	2000	2500	3000	3300	