



THREE PHASE EPS BOX-TP



Max. input current
(per phase) 32A



Safety



IP65 Rated



Quickly Installation

- Max. input current (per phase) 32A
- PC+ABS ,Robust plastic enclosure IP65
- Easy installation, plug and play
- Applied to residential, commercial solar installations
- Used with AIO 3H/AC inverter
- Automatically switch to Off-Grid state



Fox ESS EPS BOX-TP

SPECIFICATIONS

Model	EPS BOX-TP
Rated Voltage	220 / 380VAC, 230 / 400VAC, 3L / N / PE
AC Frequency	50 / 60Hz
Max. Input Current (per Phase)	32A
EPS Input	
Rated Voltage	220 / 380VAC, 230 / 400VAC, 3L / N / PE
AC Frequency	50 / 60Hz
Max. Input Current (per Phase)	25A
EPS Load	
Rated Voltage	220 / 380VAC, 230 / 400VAC, 3L / N / PE
AC Frequency	50 / 60Hz
Max. Output Current	32A
General Data	
Cooling Concept	Natural
Installation	Wall-mounted
Operating Temperature Range	-25 ~ +50°C
Dimensions (W * H * D)	340 * 223 * 170 mm
Net Weight	2.8 kg
Ingress Protection	IP65

