



Product Service

# CERTIFICATE

No. B 107662 0009 Rev. 00

**Holder of Certificate:** **FOXESS Co., Ltd.**  
Room A203, Building C, No 205  
Binghai Six Road  
New Airport Industry Area, Longwan Distrit  
325058 Wenzhou, Zhejiang  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:** **Converter  
Storage Inverter**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704092112605-00

**Valid until:** 2026-05-24

**Date,** 2021-05-25

( Zhengdong Ma )

# CERTIFICATE

No. B 107662 0009 Rev. 00

**Model(s):** AIO-AC1-3.0, AIO-AC1-3.7, AIO-AC1-4.6,  
AIO-AC1-5.0, AIO-AC1-6.0.

## Parameters:

Battery input port	
Battery voltage range:	85-210Vd.c.
Max. charge/discharge current:	40/40Ad.c.
Battery type:	Lithium-ion
AC output port	
Rated power	3000W(AIO-AC1-3.0), 3680W(AIO-AC1-3.7), 4600W(AIO-AC1-4.6), 5000W(AIO-AC1-5.0), 6000W(AIO-AC1-6.0)
Max. apparent power:	3300VA(AIO-AC1-3.0), 4048VA(AIO-AC1-3.7), 5060VA(AIO-AC1-4.6), 5500VA(AIO-AC1-5.0), 6600VA(AIO-AC1-6.0)
Nominal voltage:	220/230/240Va.c.
Nominal frequency:	50/60Hz
Max. output current:	14.4Aa.c.(AIO-AC1-3.0), 17.6Aa.c.(AIO-AC1-3.7), 22Aa.c.(AIO-AC1-4.6), 23.9Aa.c.(AIO-AC1-5.0), 28.7Aa.c.(AIO-AC1-6.0)
Power factor:	1(±0.8 adjustable)

# CERTIFICATE

No. B 107662 0009 Rev. 00

AC input port	
Nominal voltage:	220/230/240Va.c.
Nominal frequency:	50/60Hz
Max. input current:	31.8Aa.c.(AIO-AC1-3.0), 34.9Aa.c.(AIO-AC1-3.7), 43.7Aa.c.(AIO-AC1-4.6), 45.5Aa.c.(AIO-AC1-5.0), 54.6Aa.c.(AIO-AC1-6.0)
Max. apparent power:	7000VA(AIO-AC1-3.0), 7680VA(AIO-AC1-3.7), 9600VA(AIO-AC1-4.6), 10000VA(AIO-AC1-5.0), 12000VA(AIO-AC1-6.0)
EPS output port	
Nominal voltage:	220/230/240Va.c.
Nominal frequency:	50/60Hz
Max. output current:	21.7Aa.c.(AIO-AC1-3.0), 21.7Aa.c.(AIO-AC1-3.7), 26.1Aa.c.(AIO-AC1-4.6), 26.1Aa.c.(AIO-AC1-5.0), 26.1Aa.c.(AIO-AC1-6.0)
Max. apparent power:	5000VA(AIO-AC1-3.0), 5000VA(AIO-AC1-3.7), 6000VA(AIO-AC1-4.6), 6000VA(AIO-AC1-5.0), 6000VA(AIO-AC1-6.0)
General information	
Operating temperature range:	-25°C...+60°C
Inverter topology	Non-isolated
Protective class:	I
Ingress protection:	IP65
Overvoltage category:	II(DC), III(AC)

**Tested according to:** IEC 62477-1:2012  
IEC 62477-1:2012/AMD1:2016  
EN 62477-1:2012/A1:2017