



Product Service

Attestation of Conformity

No. N8A 107662 0016 Rev. 01

Holder of Certificate: **FOXESS CO., LTD.**
No.939, Jinhai Third Road
New Airport Industry Area, Longwan District
325025 Wenzhou, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Product: **Converter**
Storage Inverter

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 5040922012908-00

Date, 2022-11-21

(Zhengdong Ma)

Page 1 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 107662 0016 Rev. 01

Model(s): H1-3.0-E, H1-3.7-E, H1-4.6-E,
H1-5.0-E, H1-6.0-E.

Parameters:

PV input port	
Max. input power:	3900W(H1-3.0-E), 4680W(H1-3.7-E), 5980W(H1-4.6-E), 6500W(H1-5.0-E), 7800W(H1-6.0-E)
Absolute max. voltage:	600Vd.c.
MPPT voltage range:	80-550Vd.c.
Nominal operating voltage:	360Vd.c.
Max. input current:	13.5/13.5Ad.c.
Isc PV:	15/15Ad.c.
Battery input port	
Battery voltage range:	85-450Vd.c.
Max. charge/discharge current:	40/40Ad.c.
Battery type:	Lithium-ion
AC output port	
Rated power	3000W(H1-3.0-E), 3680W(H1-3.7-E), 4600W(H1-4.6-E), 5000W(H1-5.0-E), 6000W(H1-6.0-E)
Max. apparent power:	3300VA(H1-3.0-E), 4048VA(H1-3.7-E), 5060VA(H1-4.6-E), 5500VA(H1-5.0-E), 6600VA(H1-6.0-E)
Nominal voltage:	220/230/240Va.c.
Nominal frequency:	50/60Hz
Max. output current:	14.4Aa.c.(H1-3.0-E), 17.6Aa.c.(H1-3.7-E), 22Aa.c.(H1-4.6-E), 23.9Aa.c.(H1-5.0-E), 28.7Aa.c.(H1-6.0-E)

Page 2 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 107662 0016 Rev. 01

Power factor:	1(±0.8 adjustable)
AC input port	
Nominal voltage:	220/230/240Va.c.
Nominal frequency:	50/60Hz
Max. input current:	31.8Aa.c.(H1-3.0-E), 34.9Aa.c.(H1-3.7-E), 43.7Aa.c.(H1-4.6-E), 45.5Aa.c.(H1-5.0-E), 54.6Aa.c.(H1-6.0-E)
Max. apparent power:	7000VA(H1-3.0-E), 7680VA(H1-3.7-E), 9600VA(H1-4.6-E), 10000VA(H1-5.0-E), 12000VA(H1-6.0-E)
EPS output port	
Nominal voltage:	220/230/240Va.c.
Nominal frequency:	50/60Hz
Max. output current:	21.7Aa.c.(H1-3.0-E), 21.7Aa.c.(H1-3.7-E), 26.1Aa.c.(H1-4.6-E), 26.1Aa.c.(H1-5.0-E), 26.1Aa.c.(H1-6.0-E)
Max. apparent power:	5000VA(H1-3.0-E), 5000VA(H1-3.7-E), 6000VA(H1-4.6-E), 6000VA(H1-5.0-E), 6000VA(H1-6.0-E)
General information	
Operating temperature range:	-25°C...+60°C
Inverter topology	Non-isolated
Protective class:	I
Ingress protection:	IP65
Overvoltage category:	II(DC), III(AC)

**Tested
according to:**

EN 62109-1:2010
EN 62109-2:2011