



Product Service

Attestation of Conformity

No. N8A 107662 0018 Rev. 01

Holder of Attestation: **FOXESS CO., LTD.**
No.939, Jinhai Third Road
New Airport Industry Area, Longwan District
325025 Wenzhou, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Product: **Batteries**
Rechargeable Li-ion Battery System

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 5040922012911-00

Date, 2023-01-04

(Zhengdong Ma)

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



TUV®



Product Service

Attestation of Conformity

No. N8A 107662 0018 Rev. 01

Model(s): HS 5.2, HS 7.8, HS 10.4, HS 13,
HS 15.6, HS 18.2, HS 20.8

Parameters:

Model	HS 5.2	HS 7.8	HS 10.4	HS 13
Energy	5.12kWh	7.68kWh	10.24kWh	12.8kWh
Nominal Capacity	50 Ah	50 Ah	50 Ah	50 Ah
Max. Continuous Current	50 Ad.c.	50 Ad.c.	50 Ad.c.	50 Ad.c.
Nominal Voltage	102.4 Vd.c.	153.6 Vd.c.	204.8 Vd.c.	256 Vd.c.
Voltage Range	80-116.8 Vd.c.	120-175.2 Vd.c.	160-233.6 Vd.c.	200-292 Vd.c.
Numbers of battery controller (BMX-BOX)	1	1	1	1
Numbers of battery modules (HV2600)	2	3	4	5
Ingress Protection	IP21			
Protective class	I			
Charge Temperature	0°C...+50°C			
Discharge Temperature	-10°C...+50°C			

Model	HS 15.6	HS 18.2	HS 20.8
Energy	15.36kWh	17.92kWh	20.48kWh
Nominal Capacity	50 Ah	50 Ah	50 Ah
Max. Continuous Current	50 Ad.c.	50 Ad.c.	50 Ad.c.
Nominal Voltage	307.2 Vd.c.	358.4 Vd.c.	409.6 Vd.c.
Voltage Range	240-350.4 Vd.c.	280-408.8 Vd.c.	320-467.2 Vd.c.
Numbers of battery controller (BMX-BOX)	1	1	1
Numbers of battery modules (HV2600)	6	7	8
Ingress Protection	IP21		
Protective class	I		
Charge Temperature	0°C...+50°C		
Discharge Temperature	-10°C...+50°C		

Tested according to: EN 62477-1:2012/A12:2021

Page 2 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

